

HYDRAULIC BREAKER

Suitable excavators: 22046~66139 lbs



SPECIFICATION



Improved cushion damper to absorb repercussion from hammering and shaking absorption.
 High impact power.
 Less noise, less stress to hydraulic components as absorbing pressure fluctuation.

TERRA

BREAKER XTB SERIES
 M


| Model | | XTB130 | XTB150 | XTB180 | XTB200 | XTB220 | XTB250 |
|-------------------------------|--------|-------------|-------------|-------------|-------------|-------------|-------------|
| Carrier | Lbs | 22046-33069 | 26455-39683 | 35274-48502 | 39683-52911 | 44092-57320 | 48502-66139 |
| Weight | Lbs | 1984 | 2535 | 3197 | 3483 | 3968 | 4409 |
| Accumulator Pressure | PSI | 782 | 782 | 782 | 782 | 782 | 782 |
| Operating Pressure | PSI | 1991-2560 | 2276-2702 | 2276-2702 | 2276-2702 | 2276-2702 | 2276-2702 |
| Required Oil Flow | GPM | 21.13-36.98 | 21.13-36.98 | 26.42-40.95 | 31.70-44.91 | 31.70-50.19 | 39.63-55.48 |
| Impact Rate (Long Stroke) | BPM | 350-600 | 320-550 | 320-500 | 320-480 | 340-450 | 270-400 |
| Impact Rate (Short Stroke) | BPM | 600-900 | 400-700 | 400-650 | 400-600 | 420-550 | 330-500 |
| Chisel Diameter | Inches | 4.13 | 4.53 | 4.92 | 5.31 | 5.31 | 5.71 |
| Relief Valve Setting Pressure | PSI | 2987 | 2987 | 2987 | 2987 | 2987 | 2987 |

* The above specification may be changed without prior notice for product improvement.

Auto lubrication system (option)



Available tools



Scope of supply:

- breaker
- 2 chisels
- 2 hoses
- mounting cap
- tool kit
- manual