

HYDRAULIC BREAKER

Suitable excavators: 99208~308647 lbs



SPECIFICATION

Improved cushion damper to absorb repercussion from hammering and shaking absorption.
 High impact power.
 Less noise, less stress to hydraulic components as absorbing pressure fluctuation.

X TERRA

BREAKER XTB SERIES
XL


Model		XTB650	XTB700	XTB750	XTB1200
Carrier	Lbs	99208-176370	127868-220462	132277-220462	187393-308647
Weight	Lbs	9921	12566	15432	22046
Accumulator Pressure	PSI	782-853	782-853	782-853	782-853
Operating Pressure	PSI	2134-2702	2418-2987	2418-2987	2418-2987
Required Oil Flow	GPM	68.68-95.10	81.89-103.03	92.46-110.95	118.88-140.01
Impact Rate (Long Stroke)	BPM	270-380	280-355	280-350	250-320
Impact Rate (Short Stroke)	BPM	380-530	380-480	320-430	290-380
Chisel Diameter	Inches	7.09	7.87	8.07	9.45
Relief Valve Setting Pressure	PSI	2987	3556	3556	3556

* The above specification may be changed without prior notice for product improvement.

Auto lubrication system (option)



Available tools



Scope of supply:

- breaker
- 2 chisels
- 2 hoses
- mounting cap
- tool kit
- manual